

Lampioik 1

catalogue 2024 p. 68

ref. 131001107

EAN. 3663660169943

Model 1



Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	2
IP	65
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	No
With sensor	No
With IP55 socket	No
Cable with plug	F

[Download the installation manual](#)



Lampio 1

catalogue 2024 p. 68

ref. 131001107

EAN. 3663660169943

Model 1



Materials and finishes

Material	aluminium
Colour	Black grey - 107 - RAL 7021
Colour of the support	Black grey - 107 - RAL 7021

Logistic data

Product dimensions	H.340 L.224 P.224
Net weight	1.460 Kg
Gross weight	2.620 Kg
Package dimensions 1	H.510 L.360 P.260

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years

Lampioik 1

catalogue 2024 p. 68

ref. 131003107

EAN. 3663660169530

Model 2

Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	2
IP	65
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Lampio 1

catalogue 2024 p. 68

ref. 131003107

EAN. 3663660169530

Model 2



Materials and finishes

Material	aluminium
Colour	Black grey - 107 - RAL 7021
Colour of the support	Black grey - 107 - RAL 7021

Logistic data

Product dimensions	H.592 L.224 P.224
Net weight	1.270 Kg
Gross weight	2.580 Kg
Package dimensions 1	H.250 L.250 P.950

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years

Lampioik 1

catalogue 2024 p. 68

ref. 131007107

EAN. 3663660169684

Model 4



Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	2
IP	65
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Lampio 1

catalogue 2024 p. 68

ref. 131007107

EAN. 3663660169684

Model 4



Materials and finishes

Material	aluminium
Colour	Black grey - 107 - RAL 7021
Colour of the support	Black grey - 107 - RAL 7021

Logistic data

Product dimensions	H.1278 L.224 P.224
Net weight	1.260 Kg
Gross weight	2.290 Kg
Package dimensions 1	H.510 L.360 P.260

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years

Lampioik 1

catalogue 2024 p. 68

ref. 131005107

EAN. 3663660168960

Model 3

Technical data

Rated voltage	200 to 240 - 50/60Hz
Input voltage range	230 - 250 V AC
Driver output	-
Alimentation output	-
Class	2
IP	65
IK	-
Diffuser	Clear glass
Bulb cover	-
Source	E27
Color temperature real output	-
Real light output	- lm
Energy class	Classe de la lampe (non fournie)
IRC	-
SDCM	-
Optic	-
Dimmable	-
Ta	-
Led lifetime	-
Ambient temperature range	-10 ~50°C
UGR	-
ULR	-
THDI	-
Fixing kit	Yes
With sensor	No
With IP55 socket	No

[Download the installation manual](#)



Lampioik 1

catalogue 2024 p. 68

ref. 131005107

EAN. 3663660168960

Model 3



Materials and finishes

Material	aluminium
Colour	Black grey - 107 - RAL 7021
Colour of the support	Black grey - 107 - RAL 7021

Logistic data

Product dimensions	H.877 L.224 P.224
Net weight	1.200 Kg
Gross weight	2.200 Kg
Package dimensions 1	H.510 L.360 P.260

Certifications and warranties

CE	Yes
UL	No
EAC	Yes
RoHS	Yes
ENEC	No
Anti-corrosion	25 years (on Aluminium)
Technical	5 years
Electronics	5 years