



CARREE ST LED IP 92733 W

11045 9220 W

AVAILABLE IN
WHITE 11045 9220 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 75 x 75
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.35
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	828lm // 10W // 84lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

Options

PLASTERKIT 161
CONCRETE BOX 161
MOUNTING KIT 75

CARREE ST LED IP 92733 W

11045 9220 W

For detailed installation instructions, please consult the manual: [11045_XXXX_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	 MOUNTING KIT 75 Required
 Stucanet	 MOUNTING KIT 75 Required  PLASTERKIT 161 Required
 Wood	-
 Concrete + plaster	 PLASTERKIT 161 Required  CONCRETE BOX 161 Required
 Lintel + plaster	 PLASTERKIT 161 Required  CONCRETE BOX 161 Required
 Hollow-core slab + plaster	 PLASTERKIT 161 Required  CONCRETE BOX 161 Required
 Stretched ceiling	-

CARREE ST LED IP 92733 W

11045 9220 W

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐


CARREE ST LED IP 92733 W

11045 9220 W

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


CARREE ST LED IP 92733 W

11045 9220 W




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2/1




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2)




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1)



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1




Plasterkits



207 01 161 PLASTERKIT 161



Concrete boxes




270 11 161 CONCRETE BOX 161



CARREE ST LED IP 92733 W

11045 9220 W

Mounting kits



202 00 75 MOUNTING KIT 75





Notes:



CARREE ST OK SOFT 93045 W

11048 9030 W

AVAILABLE IN
BLACK 11048 9030 B
WHITE 11048 9030 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 75 x 75
RECESSED DEPTH (MM)	75
THICKNESS OF MOUNTING SURFACE (MM)	max.35
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 25° swiveling
INFORMATION	REFLECTOR WFL-45° EXCL.DIMMABLE LED POWER SUPPLY 500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 10,2W / CRI>90 (R9: 50) / 3000K-1800K / 1038lm
SDCM	SDCM2
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1038lm // 10,2W // 109lm/W
LED TECHNICS (LUMINAIRE)	820lm // 12W // 70lm/W

Requirements

LED POWER SUPPLY 500mA-DC DIM

Options

PLASTERKIT 161
 CONCRETE BOX 161
 MOUNTING KIT 75

CARREE ST OK SOFT 93045 W

11048 9030 W

For detailed installation instructions, please consult the manual: [11048_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	 MOUNTING KIT 75 Required
 Stucanet	 MOUNTING KIT 75 Required  PLASTERKIT 161 Required
 Wood	-
 Concrete + plaster	 PLASTERKIT 161 Required  CONCRETE BOX 161 Required
 Lintel + plaster	 PLASTERKIT 161 Required  CONCRETE BOX 161 Required
 Hollow-core slab + plaster	 PLASTERKIT 161 Required  CONCRETE BOX 161 Required
 Stretched ceiling	-

CARREE ST OK SOFT 93045 W

11048 9030 W

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐


CARREE ST OK SOFT 93045 W

11048 9030 W

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->3(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	1->5(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2	☐


CARREE ST OK SOFT 93045 W

11048 9030 W




21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

☐



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2

☐


21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1

☐


21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1->2

☐


Plasterkits



207 01 161 PLASTERKIT 161

☐


Concrete boxes



270 11 161 CONCRETE BOX 161

☐

Mounting kits



202 00 75 MOUNTING KIT 75

☐

CARREE ST OK SOFT 93045 W

11048 9030 W



Notes:



CARREE TRIMLESS LED IP 93033 S1 W

202 511 811 932 W

AVAILABLE IN
WHITE 202 511 811 932 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	75
THICKNESS OF MOUNTING SURFACE (MM)	9 or 12
INGRESS PROTECTION	IP44
WEIGHT (KG)	0.3
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	849lm // 10W // 86lm/W

Requirements	
MOUNTING KIT 75 TRIMLESS	
MOUNTING KIT 75 TRIMLESS O.F.A.	
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)	

CARREE TRIMLESS LED IP 93033 S1 W

202 511 811 932 W

For detailed installation instructions, please consult the manual: [202_511_811_XXX_HAND.pdf](#)










CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT 75 TRIMLESS	Required
 Plasterboard	 MOUNTING KIT 75 TRIMLESS	Required
 Stucanet	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required






 DELTALIGHT®

CARREE TRIMLESS LED IP 93033 S1 W



202 511 811 932 W

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐

CARREE TRIMLESS LED IP 93033 S1 W
202 511 811 932 W

	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 / 1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1-2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐

Mounting kits

	202 01 75 MOUNTING KIT 75 TRIMLESS		☐
	202 01 75 OFA MOUNTING KIT 75 TRIMLESS O.F.A.		☐



Notes:



CARREE TRIMLESS OK LED 93033 W

202 510 811 932 W

AVAILABLE IN
BLACK 202 510 811 932 B
WHITE 202 510 811 932 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	rectangle - KIT
RECESSED DEPTH (MM)	85
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 25° swiveling
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 787-1089lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1089lm // 8,6W // 127lm/W
LED TECHNICS (LUMINAIRE)	849lm // 10W // 86lm/W

Requirements

MOUNTING KIT 75 TRIMLESS
MOUNTING KIT 75 TRIMLESS O.F.A.
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

CARREE TRIMLESS OK LED 93033 W
202 510 811 932 W

For detailed installation instructions, please consult the manual: [202_510_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT 75 TRIMLESS	Required
 Plasterboard	 MOUNTING KIT 75 TRIMLESS	Required
 Stucanet	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT 75 TRIMLESS O.F.A.	Required

CARREE TRIMLESS OK LED 93033 W

202 510 811 932 W

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

☐










21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐






 DELTALIGHT®

CARREE TRIMLESS OK LED 93033 W



202 510 811 932 W

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐

CARREE TRIMLESS OK LED 93033 W
202 510 811 932 W

	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 / 1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1-2(1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1	☐

Mounting kits

	202 01 75 MOUNTING KIT 75 TRIMLESS		☐
	202 01 75 OFA MOUNTING KIT 75 TRIMLESS O.F.A.		☐



Notes:



CARREE X LED 92733 S1 N

202 20 811 922 N

AVAILABLE IN
ALU GREY 202 20 811 922 A
ANTHRACITE (DARK GREY) 202 20 811 922 N
WHITE 202 20 811 922 W



[View on website](#)



General info	
LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 75 x 75
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	max.35
INGRESS PROTECTION	IP44
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.PC CLEAR EXCL.LED POWER SUPPLY 350mA-DC
Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	599lm // 7W // 90lm/W
Requirements	
LED POWER SUPPLY 350mA-DC DIM	

CARREE X LED 92733 S1 N
202 20 811 922 N


For detailed installation instructions, please consult the manual: [202_20_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Stretched ceiling	-

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐





CARREE X LED 92733 S1 N

202 20 811 922 N

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	2(2)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->2	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->2	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2	☐

CARREE X LED 92733 S1 N

202 20 811 922 N

	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1	☐

Notes:



CARREE X LED 93033-65 S2 W



202 207 811 932 W

AVAILABLE IN

ALU GREY 202 207 811 932 A

ANTHRACITE (DARK GREY) 202 207 811 932 N

WHITE 202 207 811 932 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	square - 75 x 75
RECESSED DEPTH (MM)	80
INGRESS PROTECTION	IP65
PROTECTION AGAINST MECHANICAL IMPACT	IK03
WEIGHT (KG)	0.4
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.PC CLEAR EXCL.LED POWER SUPPLY 350mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	626lm // 7W // 94lm/W

Requirements

LED POWER SUPPLY 350mA-DC DIM

CARREE X LED 93033-65 S2 W
 202 207 811 932 W

For detailed installation instructions, please consult the manual: [202_207_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 Concrete	-
 Concrete + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

CARREE X LED 93033-65 S2 W

202 207 811 932 W

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W





☐

CARREE X LED 93033-65 S2 W

202 207 811 932 W

LED power supplies			#
	300 90 63	LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) ☐
	300 90 68	LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) ☐
	300 90 69	LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) ☐
	300 90 124	LED POWER SUPPLY MULTI-POWER DIM7	2(2) ☐
	300 90 125	LED POWER SUPPLY MULTI-POWER MINI DIM5	2(2) ☐
	21012 0010	LED POWER SUPPLY MULTI POWER	1->2 ☐
	21012 0021	LED POWER SUPPLY MULTI POWER DIM1	1->2 ☐
	21012 0035	LED POWER SUPPLY MULTI POWER DIM5	1->2 ☐
	21012 005W	LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 ☐

CARREE X LED 93033-65 S2 W
 202 207 811 932 W

	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1 ☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2) ☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1 ☐

Notes: