





DEEP RINGO Hi IP S2 B

202 014 26 B

AVAILABLE IN
BLACK 202 014 26 B
WHITE 202 014 26 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	125
THICKNESS OF MOUNTING SURFACE (MM)	max.15
INGRESS PROTECTION	IP44/20
WEIGHT (KG)	0.1
ADJUSTABILITY	non adjustable

Electrical info	
	1 x QPAR51 max.35W
CLASS	II
DIM TYPE	mains (phase cut-off)

Lightsource info	
LIGHTSOURCE NAME	GU10
MIN. DISTANCE TO LIGHTSOURCE (M)	0,5

Remarks
lamp not included

For detailed installation instructions, please consult the manual: [202_014_26_HAND.pdf](#)

DEEP RINGO Hi IP S2 B

202 014 26 B

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 Concrete	-
 Concrete + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-



Notes:



DEEP RINGO TRIMLESS LED 92733 B

202 144 811 922 B

AVAILABLE IN
BLACK 202 144 811 922 B
BRUSHED ALU 202 144 811 922 BRA
BRUSHED ANTHRACITE 202 144 811 922 BRAT
BRUSHED COPPER 202 144 811 922 BRCU
BRUSHED GOLD 202 144 811 922 BRG
BRUSHED OLD BRONZE 202 144 811 922 BROB
FLEMISH BRONZE 202 144 811 922 FBR
FLEMISH GOLD 202 144 811 922 FG
GOLD COLOURED 202 144 811 922 GC
PIANO BLACK 202 144 811 922 PB
WHITE 202 144 811 922 W



 [View on website](#)

General info		
LOCATION	indoor	
INSTALLATION	Ceiling Recessed	
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT	
RECESSED DEPTH (MM)	95	
INGRESS PROTECTION	IP20	
WEIGHT (KG)	0.3	
ADJUSTABILITY	non adjustable	
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC	

Electrical info		
CLASS	III	
DIM TYPE	depending on power supply	
ENERGY CLASS	E	
CERTIFICATES	CB, ENEC	

Lightsource info		
LIGHTSOURCE NAME	LED	
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm	
TM-30 VALUES	rf: 89 / Rg: 100	
SDCM	SDCM1	
RISKGROUP	RG1	
LM80	L90B10 > 50000	
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W	
LED TECHNICS (LUMINAIRE)	792lm // 10W // 80lm/W	

DEEP RINGO TRIMLESS LED 92733 B

202 144 811 922 B


Requirements

- MOUNTING KIT R82 TRIMLESS O.F.A.
- MOUNTING KIT AIR 101
- LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

For detailed installation instructions, please consult the manual: [202_144_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT R82 TRIMLESS CSC	Required
	 MOUNTING KIT R82 TRIMLESS WSC	Required
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR 101	Required
	 MOUNTING KIT NO AIR 101	Required
	 MOUNTING KIT SIDE AIR ONLY 1	Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 101	Required
	 MOUNTING KIT TOP AIR ONLY 1	Required
	 MOUNTING KIT TOP AIR 101	Required












9

7

 DELTALIGHT®


DEEP RINGO TRIMLESS LED 92733 B

202 144 811 922 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


DEEP RINGO TRIMLESS LED 92733 B

202 144 811 922 B




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 / 1




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2)




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1)



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1




Mounting kits



15212 2000 MOUNTING KIT R82 TRIMLESS O.F.A.



Mounting kits stretched ceiling



15212 0070 MOUNTING KIT R82 TRIMLESS CSC




15212 0150 MOUNTING KIT R82 TRIMLESS WSC



DEEP RINGO TRIMLESS LED 92733 B

202 144 811 922 B


Mounting kits side air + light



29810 0010 MOUNTING KIT SIDE AIR 101




Mounting kits top air + light



29810 0210 MOUNTING KIT TOP AIR 101




Mounting kits side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1



Mounting kits top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1



Mounting kits no air



29810 0050 MOUNTING KIT NO AIR 101



DEEP RINGO TRIMLESS LED 92733 B

202 144 811 922 B

Notes:



DEEP RINGO TRIMLESS OK LED 92733 B

202 145 811 922 B

AVAILABLE IN



BLACK 202 145 811 922 B

FLEMISH BRONZE 202 145 811 922 FBR

FLEMISH GOLD 202 145 811 922 FG

GOLD COLOURED 202 145 811 922 GC

WHITE 202 145 811 922 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	105
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 30° swiveling, 355° rotatable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	792lm // 10W // 80lm/W

Requirements

MOUNTING KIT R82 TRIMLESS O.F.A.

MOUNTING KIT AIR 102

LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

DEEP RINGO TRIMLESS OK LED 92733 B

202 145 811 922 B

For detailed installation instructions, please consult the manual: [202_145_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Plasterboard	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stucanet	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Concrete + plaster	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Lintel + plaster	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Hollow-core slab + plaster	 MOUNTING KIT R82 TRIMLESS O.F.A.	Required
 Stretched ceiling	 MOUNTING KIT R82 TRIMLESS CSC	Required
	 MOUNTING KIT R82 TRIMLESS WSC	Required
 Ventilation in plasterboard	 MOUNTING KIT SIDE AIR 102	Required
	 MOUNTING KIT NO AIR 102	Required
	 MOUNTING KIT SIDE AIR ONLY 1	Required
 Ventilation in concrete + plaster	 MOUNTING KIT NO AIR 102	Required
	 MOUNTING KIT TOP AIR ONLY 1	Required
	 MOUNTING KIT TOP AIR 102	Required

DEEP RINGO TRIMLESS OK LED 92733 B

202 145 811 922 B

FINISH YOUR SPECIFICATION

Emergency units












21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B

☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W


☐

DEEP RINGO TRIMLESS OK LED 92733 B
 202 145 811 922 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


DEEP RINGO TRIMLESS OK LED 92733 B

202 145 811 922 B




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 / 1




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2)




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1)



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1




21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1




Mounting kits



15212 2000 MOUNTING KIT R82 TRIMLESS O.F.A.



Mounting kits stretched ceiling



15212 0070 MOUNTING KIT R82 TRIMLESS CSC




15212 0150 MOUNTING KIT R82 TRIMLESS WSC



DEEP RINGO TRIMLESS OK LED 92733 B

202 145 811 922 B


Mounting kits side air + light



29810 0020 MOUNTING KIT SIDE AIR 102

☐


Mounting kits top air + light



29810 0220 MOUNTING KIT TOP AIR 102

☐


Mounting kits side air only



29810 0100 MOUNTING KIT SIDE AIR ONLY 1

☐

Mounting kits top air only



29810 0200 MOUNTING KIT TOP AIR ONLY 1

☐

Mounting kits no air



29810 0060 MOUNTING KIT NO AIR 102

☐

DEEP RINGO TRIMLESS OK LED 92733 B

202 145 811 922 B

Notes:



DEEP RINGO LED 92733 B

202 272 811 922 B

AVAILABLE IN

BLACK 202 272 811 922 B

BRUSHED ALU 202 272 811 922 BRA

BRUSHED ANTHRACITE 202 272 811 922 BRAT

BRUSHED COPPER 202 272 811 922 BRCU

BRUSHED GOLD 202 272 811 922 BRG

BRUSHED OLD BRONZE 202 272 811 922 BROB



FLEMISH BRONZE 202 272 811 922 FBR

FLEMISH GOLD 202 272 811 922 FG

GOLD COLOURED 202 272 811 922 GC

PIANO BLACK 202 272 811 922 PB

WHITE 202 272 811 922 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP43/20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	768lm // 10W // 78lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

DEEP RINGO LED 92733 B

202 272 811 922 B

For detailed installation instructions, please consult the manual: [202_272_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

DEEP RINGO LED 92733 B

202 272 811 922 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B








☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐


DEEP RINGO LED 92733 B

202 272 811 922 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->3(3) / 1->3(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->5(5) / 1->5(3)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


DEEP RINGO LED 92733 B

202 272 811 922 B




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 / 1 ☐




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2) ☐




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1) ☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1 ☐



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1 ☐

Notes:



DEEP RINGO RIBS 92733 B

202 274 811 922 B



AVAILABLE IN

BLACK 202 274 811 922 B

FLEMISH BRONZE 202 274 811 922 FBR

FLEMISH GOLD 202 274 811 922 FG

WHITE 202 274 811 922 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	768lm // 10W // 78lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM


DEEP RINGO RIBS 92733 B

202 274 811 922 B

For detailed installation instructions, please consult the manual: [202_274_811_XXX_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-












9

7






DEEP RINGO RIBS 92733 B

202 274 811 922 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐

DEEP RINGO RIBS 92733 B

202 274 811 922 B

	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	2 / 1 ☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1-2(2) ☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1-2(1) ☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1 ☐
	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1 ☐

Notes:



MINI DEEP RINGO II 92718 FG

19423 9210 FG



AVAILABLE IN

BLACK 19423 9210 B

FLEMISH BRONZE 19423 9210 FBR

FLEMISH GOLD 19423 9210 FG

WHITE 19423 9210 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 56
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR SP-18° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	634lm // 10W // 64lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

MINI DEEP RINGO II 92718 FG

19423 9210 FG

For detailed installation instructions, please consult the manual: [19423_XXX0_HAND.pdf](#)










CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

MINI DEEP RINGO II 92718 FG


19423 9210 FG

FINISH YOUR SPECIFICATION

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(2) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(2) / 1->2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(2) / 1->2(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2 / 1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->3 / 1->3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->3 / 1->3	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->3 / 1->3	☐


MINI DEEP RINGO II 92718 FG

19423 9210 FG




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

☐



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

☐



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

☐



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2

☐



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1->2 / 1->2

☐



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

1

☐



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8

1

☐



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1 -> 2(2)

☐


21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1 -> 2(1)

☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1->2

☐

MINI DEEP RINGO II 92718 FG

19423 9210 FG



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1->2



Notes:



MINI DEEP RINGO II X 93037 FBRX

19424 9330 FBRX



AVAILABLE IN

BLACK 19424 9330 B

FLEMISH BRONZE OUTDOOR 19424 9330 FBRX

ANTHRACITE (DARK GREY) 19424 9330 N

WHITE 19424 9330 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 56
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP65
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-37° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 52) / 3000K / 734-1018lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1018lm // 8,6W // 118lm/W
LED TECHNICS (LUMINAIRE)	678lm // 10W // 69lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

For detailed installation instructions, please consult the manual: [19424_XXX0_HAND.pdf](#)

MINI DEEP RINGO II X 93037 FBRX

19424 9330 FBRX

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-


MINI DEEP RINGO II X 93037 FBRX

19424 9330 FBRX

FINISH YOUR SPECIFICATION

LED power supplies


#



300 90 63

LED POWER SUPPLY MULTI-POWER DIM9


1->4(4) / 1->4(3)

☐


300 90 68

LED POWER SUPPLY MULTI-POWER DIM5


1->2(2) / 1->2(1)

☐


300 90 69

LED POWER SUPPLY MULTI-POWER HV DIM9


2->6(6) / 1->6(4)

☐


300 90 124

LED POWER SUPPLY MULTI-POWER DIM7


1->2(2) / 1->2(1)

☐


300 90 125

LED POWER SUPPLY MULTI-POWER MINI DIM5


1->2(2) / 1->2(1)

☐


21012 0010

LED POWER SUPPLY MULTI POWER


1->2 / 1->2

☐


21012 0021

LED POWER SUPPLY MULTI POWER DIM1


1->3 / 1->3

☐


21012 0035

LED POWER SUPPLY MULTI POWER DIM5

1->3 / 1->3

☐


21012 005W


LED POWER SUPPLY MULTI-POWER COMPACT WDL

1->3 / 1->3

☐


MINI DEEP RINGO II X 93037 FBRX

19424 9330 FBRX




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

☐



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

☐



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

☐



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2

☐



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1->2 / 1->2

☐



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

1

☐



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8

1

☐



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1 -> 2(2)

☐


21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1 -> 2(1)

☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1->2

☐

MINI DEEP RINGO II X 93037 FBRX

19424 9330 FBRX



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1->2



Notes:



MINI DEEP RINGO II OK 92725 FG

19425 9220 FG



AVAILABLE IN

BLACK 19425 9220 B

FLEMISH BRONZE 19425 9220 FBR

FLEMISH GOLD 19425 9220 FG

WHITE 19425 9220 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 71
RECESSED DEPTH (MM)	80
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	0° to 30° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-25° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	676lm // 10W // 68lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

MINI DEEP RINGO II OK 92725 FG

19425 9220 FG

For detailed installation instructions, please consult the manual: [19425_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

MINI DEEP RINGO II OK 92725 FG

19425 9220 FG

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐


MINI DEEP RINGO II OK 92725 FG

19425 9220 FG

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(2) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(2) / 1->2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(2) / 1->2(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2 / 1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->3 / 1->3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->3 / 1->3	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->3 / 1->3	☐


MINI DEEP RINGO II OK 92725 FG

19425 9220 FG




21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8

1

☐



21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8

2->2

☐



21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8

1

☐



21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8

2->2

☐



21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

1->2 / 1->2

☐



21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8

1

☐



21012 0318 LED POWER SUPPLY 500mA / 10W DIM8

1

☐



21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1 -> 2(2)

☐


21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1 -> 2(1)

☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1->2

☐

MINI DEEP RINGO II OK 92725 FG

19425 9220 FG



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1->2



Notes:



DEEP RINGO X 92733 B

19434 9220 B



AVAILABLE IN

BLACK 19434 9220 B

FLEMISH BRONZE OUTDOOR 19434 9220 FBRX

ANTHRACITE (DARK GREY) 19434 9220 N

WHITE 19434 9220 W



[View on website](#)



General info

LOCATION	indoor-outdoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	90
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP65
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, EAC, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	768lm // 10W // 78lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM


DEEP RINGO X 92733 B

19434 9220 B

For detailed installation instructions, please consult the manual: [19434_XXXX_HAND.pdf](#)

CEILING COMPATIBILITY

Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-












9

7


DEEP RINGO X 92733 B

19434 9220 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


DEEP RINGO X 92733 B

19434 9220 B




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 / 1 ☐




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2) ☐




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1) ☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1 ☐



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1 ☐

Notes:



DEEP RINGO OK LED 92733 B

19435 9220 B

AVAILABLE IN



BLACK 19435 9220 B

FLEMISH BRONZE 19435 9220 FBR

FLEMISH GOLD 19435 9220 FG

GOLD COLOURED 19435 9220 GC

WHITE 19435 9220 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - 76
RECESSED DEPTH (MM)	100
THICKNESS OF MOUNTING SURFACE (MM)	min.5
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.3
ADJUSTABILITY	0° to 30° swiveling, 360° rotatable
INFORMATION	REFLECTOR FL-33° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 753-1041lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	1041lm // 8,6W // 121lm/W
LED TECHNICS (LUMINAIRE)	691lm // 10W // 70lm/W

Requirements

LED POWER SUPPLY 350 / 500mA-DC DIM

DEEP RINGO OK LED 92733 B

19435 9220 B

For detailed installation instructions, please consult the manual: [19435_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY


Ceiling Type	Mounting Kit
 System ceiling	-
 Plasterboard	-
 Stucanet	-
 Wood	-
 Concrete	-
 Concrete + plaster	-
 Lintel + plaster	-
 Hollow-core slab	-
 Hollow-core slab + plaster	-
 Stretched ceiling	-

DEEP RINGO OK LED 92733 B

19435 9220 B

FINISH YOUR SPECIFICATION

Emergency units



21032 0270 B EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER B










☐

21032 0270 W EMERGENCY UNIT 7W / 1h + LED INDICATOR HOLDER W

☐


DEEP RINGO OK LED 92733 B

19435 9220 B

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(4)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(1) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(1) / 1(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(1) / 1(1)	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->2 / 1->2	☐
	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐


DEEP RINGO OK LED 92733 B

19435 9220 B




21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8

2 / 1 ☐




21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68

1-2(2) ☐




21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68

1-2(1) ☐



21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5

1 ☐



21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5

1 ☐



Notes:



MINI DEEP RINGO II TRIMLESS 92737 W

19439 9230 W

AVAILABLE IN
BLACK 19439 9230 B
WHITE 19439 9230 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Recessed
CUTOUT SHAPE/SIZE (MM)	round - Ø KIT
RECESSED DEPTH (MM)	95
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.2
ADJUSTABILITY	non adjustable
INFORMATION	TUBE 52 BLACK or WHITE included Other TUBE 52 colours optional REFLECTOR WFL-37° EXCL.LED POWER SUPPLY 350-500mA-DC

Electrical info

CLASS	III
DIM TYPE	depending on type of external power supply
ENERGY CLASS	F

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8-8,6W / CRI>90 (R9: 60) / 2700K / 702-974lm
TM-30 VALUES	Rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	974lm // 8,6W // 113lm/W
LED TECHNICS (LUMINAIRE)	694lm // 10W // 70lm/W

Requirements

MOUNTING KIT MINI DEEP RINGO II TRIMLESS
LED POWER SUPPLY 350 / 500mA-DC DIM (Remote)

Options

TUBE 52

MINI DEEP RINGO II TRIMLESS 92737 W
 19439 9230 W










For detailed installation instructions, please consult the manual: [19439_XXX0_HAND.pdf](#)

CEILING COMPATIBILITY











Ceiling Type	Mounting Kit	
 System ceiling	 MOUNTING KIT MINI DEEP RINGO II TRIMLESS	Required
 Plasterboard	 MOUNTING KIT MINI DEEP RINGO II TRIMLESS	Required
 Stucanet	 MOUNTING KIT MINI DEEP RINGO II TRIMLESS	Required

MINI DEEP RINGO II TRIMLESS 92737 W
19439 9230 W


FINISH YOUR SPECIFICATION

LED power supplies			#
	300 90 63 LED POWER SUPPLY MULTI-POWER DIM9	1->4(4) / 1->4(3)	☐
	300 90 68 LED POWER SUPPLY MULTI-POWER DIM5	1->2(2) / 1->2(1)	☐
	300 90 69 LED POWER SUPPLY MULTI-POWER HV DIM9	2->6(6) / 1->6(4)	☐
	300 90 124 LED POWER SUPPLY MULTI-POWER DIM7	1->2(2) / 1->2(1)	☐
	300 90 125 LED POWER SUPPLY MULTI-POWER MINI DIM5	1->2(2) / 1->2(1)	☐
	21012 0010 LED POWER SUPPLY MULTI POWER	1->2 / 1->2	☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1->3 / 1->3	☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1->3 / 1->3	☐
	21012 005W LED POWER SUPPLY MULTI-POWER COMPACT WDL	1->3 / 1->3	☐


MINI DEEP RINGO II TRIMLESS 92737 W
19439 9230 W

	21012 0258 LED POWER SUPPLY MULTI POWER 200-350 / 10W DIM8	1	☐
	21012 0268 LED POWER SUPPLY MULTI POWER 200-350 / 15W DIM8	2->2	☐
	21012 0278 LED POWER SUPPLY MULTI POWER 500-700 / 20W DIM8	1	☐
	21012 0288 LED POWER SUPPLY MULTI POWER 500-700 / 36W DIM8	2->2	☐
	21012 0298 LED POWER SUPPLY MULTI POWER 250-900 / 20W DIM8	1->2 / 1->2	☐
	21012 0308 LED POWER SUPPLY 350mA / 7,35W DIM8	1	☐
	21012 0318 LED POWER SUPPLY 500mA / 10W DIM8	1	☐
	21012 0480 LED POWER SUPPLY 350mA-DC / 17W IP68	1 -> 2 (2)	☐
	21012 0500 LED POWER SUPPLY 500mA-DC / 24W IP68	1 -> 2 (1)	☐
	21032 0295 LED POWER CONVERTER 48V-DC to 350 mA-DC / 15W DIM5	1->2	☐

MINI DEEP RINGO II TRIMLESS 92737 W
 19439 9230 W

	21032 0305 LED POWER CONVERTER 48V-DC to 500 mA-DC / 22W DIM5	1->2	☐
--	--	------	--------------------------

Mounting kits

	19410 0010 MOUNTING KIT MINI DEEP RINGO II TRIMLESS	☐
--	--	--------------------------

Decorative ornaments

	19810 0230 B TUBE 52 B	☐
	19810 0230 DC TUBE 52 DC	☐
	19810 0230 FBR TUBE 52 FBR	☐
	19810 0230 FG TUBE 52 FG	☐
	19810 0230 GC TUBE 52 GC	☐
	19810 0230 W TUBE 52 W	☐

Notes: