



## SUPERNOVA LINE 65 TRIMLESS 930

20628 9300



[View on website](#)



### General info

|                                           |                                      |
|-------------------------------------------|--------------------------------------|
| <b>LOCATION</b>                           | indoor                               |
| <b>INSTALLATION</b>                       | Ceiling Recessed                     |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | round - 685                          |
| <b>RECESSED DEPTH (MM)</b>                | 200                                  |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | max.25                               |
| <b>INGRESS PROTECTION</b>                 | IP20                                 |
| <b>WEIGHT (KG)</b>                        | 7.6                                  |
| <b>ADJUSTABILITY</b>                      | non adjustable                       |
| <b>INFORMATION</b>                        | INCL.PC SBL<br>INCL.LED POWER SUPPLY |

### Electrical info

|                              |                      |
|------------------------------|----------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz |
| <b>CLASS</b>                 | I                    |
| <b>POWER SUPPLY INCLUDED</b> | YES                  |
| <b>DIM TYPE</b>              | non-dimmable         |
| <b>ENERGY CLASS</b>          | D                    |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 58,8W / CRI>90 (R9: 50) / 3000K / 8635lm |
| <b>TM-30 VALUES</b>                | Rf: 92 / Rg: 100                                     |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>RISKGROUP</b>                   | RG2                                                  |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 8635lm // 58,8W // 147lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 6165lm // 68W // 91lm/W                              |

For detailed installation instructions, please consult the manual: [20628\\_XXX0\\_HAND.pdf](#)

**SUPERNOVA LINE 65 TRIMLESS 930**  
 20628 9300



CEILING COMPATIBILITY

| Ceiling Type                                                                                           | Mounting Kit |
|--------------------------------------------------------------------------------------------------------|--------------|
|  <b>System ceiling</b> | -            |
|  <b>Plasterboard</b>   | -            |

Notes:



SUPERNOVA LINE 125 TRIMLESS  
930 DIM1  
20630 9301



 [View on website](#)



| General info                       |                                               |
|------------------------------------|-----------------------------------------------|
| LOCATION                           | indoor                                        |
| INSTALLATION                       | Ceiling Recessed                              |
| CUTOUT SHAPE/SIZE (MM)             | round - 1285                                  |
| RECESSED DEPTH (MM)                | 200                                           |
| THICKNESS OF MOUNTING SURFACE (MM) | max.25                                        |
| INGRESS PROTECTION                 | IP20                                          |
| WEIGHT (KG)                        | 22.9                                          |
| ADJUSTABILITY                      | non adjustable                                |
| INFORMATION                        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY |

| Electrical info |                      |
|-----------------|----------------------|
| ELECTRICAL      | 220-240V / 0 50-60Hz |
| CLASS           | I                    |
| POWER SUPPLY    | YES                  |
| DIM TYPE        | 1-10V                |
| ENERGY CLASS    | D                    |

| Lightsource info            |                                                       |
|-----------------------------|-------------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                                   |
| LIGHTSOURCE                 | LED cluster 235,2W / CRI>90 (R9: 50) / 3000K / 3454lm |
| TM-30 VALUES                | Rf: 92 / Rg: 100                                      |
| SDCM                        | SDCM3                                                 |
| RISKGROUP                   | RG2                                                   |
| LM80                        | L80 > 60000                                           |
| LED TECHNICS (LIGHT SOURCE) | 3454lm // 235,2W // 147lm/W                           |
| LED TECHNICS (LUMINAIRE)    | 26527lm // 270W // 98lm/W                             |

| Options                  |  |
|--------------------------|--|
| WIRELESS CONTROL 5A DIM1 |  |

For detailed installation instructions, please consult the manual: [20630\\_XXX1\\_HAND.pdf](#)


**SUPERNOVA LINE 125 TRIMLESS 930 DIM1**  
20630 9301

**CEILING COMPATIBILITY**

| Ceiling Type                                                                                    | Mounting Kit |
|-------------------------------------------------------------------------------------------------|--------------|
|  System ceiling | -            |
|  Plasterboard   | -            |

**FINISH YOUR SPECIFICATION**

**Miscellaneous control equipment**



|                                                                                   |                                                |                          |
|-----------------------------------------------------------------------------------|------------------------------------------------|--------------------------|
|  | <b>300 90 016 ED1</b> WIRELESS CONTROL 5A DIM1 | <input type="checkbox"/> |
|-----------------------------------------------------------------------------------|------------------------------------------------|--------------------------|

Notes:



SUPERNOVA LINE TRIMLESS 65 TW  
WD

274 89 06 26 WD



 [View on website](#)



General info

|                                    |                                                                              |
|------------------------------------|------------------------------------------------------------------------------|
| LOCATION                           | indoor                                                                       |
| INSTALLATION                       | Ceiling Recessed                                                             |
| CUTOUT SHAPE/SIZE (MM)             | round - 685                                                                  |
| RECESSED DEPTH (MM)                | 200                                                                          |
| THICKNESS OF MOUNTING SURFACE (MM) | max.25                                                                       |
| INGRESS PROTECTION                 | IP20                                                                         |
| WEIGHT (KG)                        | 6.6                                                                          |
| ADJUSTABILITY                      | non adjustable                                                               |
| INFORMATION                        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY<br>HUMAN CENTRIC LIGHT CONTROL |

Electrical info

|                       |                         |
|-----------------------|-------------------------|
| ELECTRICAL            | 120-240V / 0 50-60Hz    |
| CLASS                 | I                       |
| POWER SUPPLY INCLUDED | YES                     |
| DIM TYPE              | WDL = wireless dimmable |
| ENERGY CLASS          | F                       |
| CERTIFICATES          | CB, EAC, ENEC, RCM      |

Lightsource info

|                             |                                                                                                                               |
|-----------------------------|-------------------------------------------------------------------------------------------------------------------------------|
| LIGHTSOURCE NAME            | LED                                                                                                                           |
| LIGHTSOURCE                 | @ 2700K: LED cluster 45W / CRI>80 / 2700K - 5700K / 4208lm<br>Or<br>@ 5700K:LED cluster 45W / CRI>80 / 2700K - 5700K / 4841lm |
| LED TECHNICS (LIGHT SOURCE) | @ 2700K: 4208 lm // 45 W // 94 lm/W<br>Or<br>@ 5700K: 4841 lm // 45 W // 108 lm/W                                             |
| LED TECHNICS (LUMINAIRE)    | 3131lm // 52W // 60lm/W<br>Or<br>3592lm // 52W // 69lm/W                                                                      |

For detailed installation instructions, please consult the manual: [274\\_89\\_06\\_26\\_WD\\_HAND.pdf](#)

**SUPERNOVA LINE TRIMLESS 65 TW WD**  
 274 89 06 26 WD

CEILING COMPATIBILITY



| Ceiling Type                                                                                           | Mounting Kit |
|--------------------------------------------------------------------------------------------------------|--------------|
|  <b>System ceiling</b> | -            |
|  <b>Plasterboard</b>   | -            |

Notes:



## SUPERNOVA LINE TRIMLESS 125 TW WD

274 89 12 26 WD



[View on website](#)

### General info

|                                           |                                                                              |
|-------------------------------------------|------------------------------------------------------------------------------|
| <b>LOCATION</b>                           | indoor                                                                       |
| <b>INSTALLATION</b>                       | Ceiling Recessed                                                             |
| <b>CUTOUT SHAPE/SIZE (MM)</b>             | round - 1285                                                                 |
| <b>RECESSED DEPTH (MM)</b>                | 200                                                                          |
| <b>THICKNESS OF MOUNTING SURFACE (MM)</b> | max.25                                                                       |
| <b>INGRESS PROTECTION</b>                 | IP20                                                                         |
| <b>WEIGHT (KG)</b>                        | 10.8                                                                         |
| <b>ADJUSTABILITY</b>                      | non adjustable                                                               |
| <b>INFORMATION</b>                        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY<br>HUMAN CENTRIC LIGHT CONTROL |

### Electrical info

|                     |                         |
|---------------------|-------------------------|
| <b>ELECTRICAL</b>   | 120-240V / 0 50-60Hz    |
| <b>CLASS</b>        | I                       |
| <b>POWER SUPPLY</b> | YES                     |
| <b>DIM TYPE</b>     | WDL = wireless dimmable |
| <b>ENERGY CLASS</b> | F                       |
| <b>CERTIFICATES</b> | CB, EAC, ENEC, RCM      |

### Lightsource info

|                                    |                                                                                                                                    |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                                |
| <b>LIGHTSOURCE</b>                 | @ 2700K: LED cluster 179W / CRI>80 / 2700K - 5700K / 16942lm<br>Or<br>@ 5700K: LED cluster 179W / CRI>80 / 2700K - 5700K / 19338lm |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | @ 2700K: 16942 lm // 179 W // 95 lm/W<br>Or<br>@ 5700K: 19338 lm // 179 W // 108 lm/W                                              |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 13469lm // 206W // 65lm/W<br>Or<br>15316lm // 206W // 74lm/W                                                                       |

For detailed installation instructions, please consult the manual: [274\\_89\\_12\\_26\\_WD\\_HAND.pdf](#)

**SUPERNOVA LINE TRIMLESS 125 TW WD**  
 274 89 12 26 WD

CEILING COMPATIBILITY

| Ceiling Type                                                                                           | Mounting Kit |
|--------------------------------------------------------------------------------------------------------|--------------|
|  <b>System ceiling</b> | -            |
|  <b>Plasterboard</b>   | -            |

Notes: