



CONFORM P14 DOWN-UP 953067 DIM4 B-B



26511 7324 B-B

AVAILABLE IN

BLACK-BLACK 26511 7324 B-B

BLACK-GOLD MATT 26511 7324 B-MMAT

WHITE-BLACK 26511 7324 W-B



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.2
ADJUSTABILITY	non adjustable
INFORMATION	60 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 650mA-DC DOWN / 500mA-DC UP 2 DALI CONTROL CHANNELS INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm ² NATURAL LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22W / CRI>95 (R9: 80) / 3000K / 2568lm UP: LED cluster 16,8W / CRI>95 (R9: 80) / 3000K / 1978lm
TM-30 VALUES	Rf: 94 / Rg: 103
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 2568lm // 22W // 117lm/W UP: 1978lm // 16,8W // 117lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 1613lm // 25W // 64lm/W UP: 1559lm // 19W // 81lm/W

CONFORM P14 DOWN-UP 953067 DIM4 B-B

26511 7324 B-B

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS


For detailed installation instructions, please consult the manual: [**26511_XXX4_HAND.pdf**](#)

CONFORM P14 DOWN-UP 953067 DIM4 B-B

26511 7324 B-B

FINISH YOUR SPECIFICATION

Current supply



203 99 55 ANO

CABLE BASE R ANO

☐

203 99 55 B

CABLE BASE R B

☐

203 99 55 W

CABLE BASE R W

☐



203 99 56 ANO

CABLE BASE S ANO

☐

203 99 56 B

CABLE BASE S B


☐

203 99 56 W

CABLE BASE S W

☐

Coversets



204 00 100 B

COVERSET R 100 B

☐

204 00 100 W


COVERSET R 100 W

☐


CONFORM P14 DOWN-UP 953067 DIM4 B-B

26511 7324 B-B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐


15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes:



CONFORM P20 DOWN-UP 953067 DIM4 B-B



26512 7324 B-B

AVAILABLE IN

BLACK-BLACK 26512 7324 B-B

BLACK-GOLD MATT 26512 7324 B-MMAT

WHITE-BLACK 26512 7324 W-B



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	5.4
ADJUSTABILITY	non adjustable
INFORMATION	84 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 900mA-DC DOWN / 700mA-DC UP 2 DALI CONTROL CHANNELS INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm ² NATURAL LIGHT TECHNOLOGY

Electrical info

ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 30,5W / CRI>95 (R9: 80) / 3000K / 3570lm UP: LED cluster 23,1W / CRI>95 (R9: 80) / 3000K / 2842lm
TM-30 VALUES	Rf: 94 / Rg: 103
SDCM	SDCM3
RISKGROUP	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3570lm // 30,5W // 117lm/W UP: 2842lm // 23,1W // 123lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2242lm // 35W // 64lm/W UP: 2239lm // 27W // 84lm/W

CONFORM P20 DOWN-UP 953067 DIM4 B-B

26512 7324 B-B

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS

SUSPENSION ST / SUSPENSION TRIMLESS


For detailed installation instructions, please consult the manual: [26512_XXX4_HAND.pdf](#)

CONFORM P20 DOWN-UP 953067 DIM4 B-B

26512 7324 B-B

FINISH YOUR SPECIFICATION

Current supply



41

203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐



41

203 99 56 ANO CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B


☐

204 00 100 W COVERSET R 100 W


☐

CONFORM P20 DOWN-UP 953067 DIM4 B-B
26512 7324 B-B

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐


15225 0340 B SUSPENSION ST B

☐

15225 0340 W SUSPENSION ST W

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W

☐

Notes:



CONFORM P28 DOWN-UP 953067 DIM4 B-B



26513 7324 B-B

AVAILABLE IN

BLACK-BLACK 26513 7324 B-B

BLACK-GOLD MATT 26513 7324 B-MMAT

WHITE-BLACK 26513 7324 W-B



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	7.8
ADJUSTABILITY	non adjustable
INFORMATION	120 x REFLECTOR FL-67° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 1300mA-DC DOWN / 1000mA-DC UP 2 DALI CONTROL CHANNELS INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 5 x 0.75mm ² NATURAL LIGHT TECHNOLOGY
Electrical info	
ELECTRICAL	220-240V / 0 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI or DSI or push button
ENERGY CLASS	D
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 43,9W / CRI>95 (R9: 80) / 3000K / 5136lm UP: LED cluster 33,7W / CRI>95 (R9: 80) / 3000K / 3955lm
TM-30 VALUES	Rf: 94 / Rg: 103
SDCM	SDCM3
RISKGROUPE	RG2
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 5136lm // 43,9W // 117lm/W UP: 3955lm // 33,7W // 117lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 3225lm // 50W // 64lm/W UP: 3117lm // 39W // 80lm/W

CONFORM P28 DOWN-UP 953067 DIM4 B-B

26513 7324 B-B

Options

CABLE BASE R / S

COVERSET R 62-90-100 / S 62-80-90

CONNECTION ST / CONNECTION TRIMLESS


SUSPENSION ST / SUSPENSION TRIMLESS

For detailed installation instructions, please consult the manual: [**26513_XXX4_HAND.pdf**](#)

CONFORM P28 DOWN-UP 953067 DIM4 B-B
26513 7324 B-B

FINISH YOUR SPECIFICATION

Current supply



41

203 99 55 ANO CABLE BASE R ANO

☐

203 99 55 B CABLE BASE R B

☐

203 99 55 W CABLE BASE R W

☐



41

203 99 56 ANO CABLE BASE S ANO

☐


203 99 56 B CABLE BASE S B

☐

203 99 56 W CABLE BASE S W

☐

Coversets



204 00 100 B COVERSET R 100 B

☐


204 00 100 W COVERSET R 100 W

☐

CONFORM P28 DOWN-UP 953067 DIM4 B-B

26513 7324 B-B

Suspension parts



328 10 01

SUSPENSION TRIMLESS O.F.A.

☐

15225 0340 B

SUSPENSION ST B


☐

15225 0340 W

SUSPENSION ST W

☐

Electric connection parts



328 10 03

CONNECTION TRIMLESS O.F.A.

☐

15225 0360 B

CONNECTION ST B

☐

15225 0360 W

CONNECTION ST W

☐

Notes: