



INFORM R1+ CS DOWN 92748 DIM5 B-B

26815 9225 B-B

AVAILABLE IN



BLACK-BLACK 26815 9225 B-B

BLACK-GOLD MATT 26815 9225 B-MMAT

FLEMISH GOLD-BLACK 26815 9225 FG-B

WHITE-BLACK 26815 9225 W-B

WHITE-WHITE 26815 9225 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.3
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3456lm // 22,9W // 151lm/W
LED TECHNICS (LUMINAIRE)	2886lm // 26W // 110lm/W

For detailed installation instructions, please consult the manual: [26815_XXX5_HAND.pdf](#)



INFORM R1+ CS DOWN 92748 DIM5 B-B

26815 9225 B-B

Notes:



INFORM R1+ CS DOWN 93048 DIM5 W-B

26815 9325 W-B

AVAILABLE IN



BLACK-BLACK 26815 9325 B-B

BLACK-GOLD MATT 26815 9325 B-MMAT

FLEMISH GOLD-BLACK 26815 9325 FG-B

WHITE-BLACK 26815 9325 W-B

WHITE-WHITE 26815 9325 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.3
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° INCL.DIMMABLE LED POWER SUPPLY 700mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3504lm // 22,9W // 153lm/W
LED TECHNICS (LUMINAIRE)	2926lm // 26W // 111lm/W

For detailed installation instructions, please consult the manual: [26815_XXX5_HAND.pdf](#)



INFORM R1+ CS DOWN 93048 DIM5 W-B

26815 9325 W-B

Notes:

INFORM R1+ CS DOWN-UP 92748 DIM5 W-W

26816 9225 W-W

AVAILABLE IN



BLACK-BLACK 26816 9225 B-B

BLACK-GOLD MATT 26816 9225 B-MMAT

FLEMISH GOLD-BLACK 26816 9225 FG-B

WHITE-BLACK 26816 9225 W-B

WHITE-WHITE 26816 9225 W-W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 700mA-DC 2 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 2700K / 3456lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 2700K / 1728lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3456lm // 22,9W // 151lm/W UP: 1728lm // 11,5W // 151lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2761lm // 26W // 105lm/W UP: 1106lm // 13W // 84lm/W



INFORM R1+ CS DOWN-UP 92748 DIM5 W-W

26816 9225 W-W

For detailed installation instructions, please consult the manual: **26816_XXX5_HAND.pdf**

Notes:

INFORM R1+ CS DOWN-UP 93048 DIM5 FG-B

26816 9325 FG-B

AVAILABLE IN



BLACK-BLACK 26816 9325 B-B

BLACK-GOLD MATT 26816 9325 B-MMAT

FLEMISH GOLD-BLACK 26816 9325 FG-B

WHITE-BLACK 26816 9325 W-B

WHITE-WHITE 26816 9325 W-W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	4.5
ADJUSTABILITY	non adjustable
INFORMATION	96 x REFLECTOR WFL-71° (DOWN) INCL.DIMMABLE LED POWER SUPPLY 700mA-DC 2 DALI CONTROL CHANNELS INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m POWER VIA CABLE SUSPENSION

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	DALI
ENERGY CLASS	C
CERTIFICATES	CB, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	DOWN: LED cluster 22,9W / CRI>90 (R9: 50) / 3000K / 3504lm UP: LED cluster 11,5W / CRI>90 (R9: 50) / 3000K / 1752lm
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	DOWN: 3504lm // 22,9W // 153lm/W UP: 1752lm // 11,5W // 153lm/W
LED TECHNICS (LUMINAIRE)	DOWN: 2800lm // 26W // 106lm/W UP: 1121lm // 13W // 85lm/W



INFORM R1+ CS DOWN-UP 93048 DIM5 FG-B

26816 9325 FG-B

For detailed installation instructions, please consult the manual: **26816_XXX5_HAND.pdf**

Notes: