





LASS-OH! 6060 93034 GC
24811 9320 GC

AVAILABLE IN
BLACK 24811 9320 B
GOLD COLOURED 24811 9320 GC



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.4 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 700mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED cluster 6,1W / CRI>90 (R9: 50) / 3000K / 683lm)
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2732lm // 24,4W // 112lm/W
LED TECHNICS (LUMINAIRE)	2159lm // 28W // 77lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 700mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

LASS-OH! 6060 93034 GC

24811 9320 GC

Accessories



JIHA S

For detailed installation instructions, please consult the manual: [24811_XXXX_HAND.pdf](#)

LASS-OH! 6060 93034 GC
24811 9320 GC




FINISH YOUR SPECIFICATION

Current supply







	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

#

	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐


LASS-OH! 6060 93034 GC
 24811 9320 GC

Power box		#
 24814 0010 B LASS-OH! POWERBOX B	1	☐
 24814 0011 B LASS-OH! POWERBOX DIM1 B	1	☐
 24814 0015 B LASS-OH! POWERBOX DIM5 B	1	☐
Coversets		
 204 00 100 B COVERSET R 100 B		☐
204 00 100 W COVERSET R 100 W		☐
Suspension parts		
 328 10 01 SUSPENSION TRIMLESS O.F.A.		☐
 15225 0340 B SUSPENSION ST B		☐
15225 0340 W SUSPENSION ST W		☐


LASS-OH! 6060 93034 GC

24811 9320 GC

Electric connection parts

	328 10 03	CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B	CONNECTION ST B	☐
	15225 0360 W	CONNECTION ST W	☐

Light altering devices



	24814 0020 B	JIHA! S B	☐
--	---------------------	-----------	--------------------------

Notes:



LASS-OH! 60110 92734 B
24812 9220 B

AVAILABLE IN
BLACK 24812 9220 B
GOLD COLOURED 24812 9220 GC



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	INCL.4 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 700mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2660lm // 24,4W // 109lm/W
LED TECHNICS (LUMINAIRE)	2102lm // 28W // 75lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 700mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

LASS-OH! 60110 92734 B

24812 9220 B

Accessories



JIHA S/R

For detailed installation instructions, please consult the manual: [24812_XXXX_HAND.pdf](#)

LASS-OH! 60110 92734 B
24812 9220 B




FINISH YOUR SPECIFICATION

Current supply







	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

#


	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐

LASS-OH! 60110 92734 B
24812 9220 B

Power box		#
	24814 0010 B LASS-OH! POWERBOX B	1 ☐
	24814 0011 B LASS-OH! POWERBOX DIM1 B	1 ☐
	24814 0015 B LASS-OH! POWERBOX DIM5 B	1 ☐
Coversets		
	204 00 100 B COVERSET R 100 B	☐
	204 00 100 W COVERSET R 100 W	☐
Suspension parts		
	328 10 01 SUSPENSION TRIMLESS O.F.A.	☐
	15225 0340 B SUSPENSION ST B	☐
	15225 0340 W SUSPENSION ST W	☐


LASS-OH! 60110 92734 B
24812 9220 B

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐




15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W


☐

Light altering devices



24814 0020 B JIHA! S B

☐



24814 0030 B JIHA! R B

☐



Notes:



LASS-OH! 60160 92734 B

24813 9220 B

AVAILABLE IN
BLACK 24813 9220 B
GOLD COLOURED 24813 9220 GC



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.6 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.4 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	6 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3990lm // 36,6W // 109lm/W
LED TECHNICS (LUMINAIRE)	3153lm // 42W // 75lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 1050mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

LASS-OH! 60160 92734 B

24813 9220 B

Accessories



JIHA S/R

For detailed installation instructions, please consult the manual: [24813_XXXX_HAND.pdf](#)

LASS-OH! 60160 92734 B
24813 9220 B




FINISH YOUR SPECIFICATION

Current supply







	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

#


	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐

LASS-OH! 60160 92734 B
 24813 9220 B

Power box		#
 24814 0010 B LASS-OH! POWERBOX B	1	☐
 24814 0011 B LASS-OH! POWERBOX DIM1 B	1	☐
 24814 0015 B LASS-OH! POWERBOX DIM5 B	1	☐
Coversets		
 204 00 100 B COVERSET R 100 B		☐
204 00 100 W COVERSET R 100 W		☐
Suspension parts		
 328 10 01 SUSPENSION TRIMLESS O.F.A.		☐
 15225 0340 B SUSPENSION ST B		☐
15225 0340 W SUSPENSION ST W		☐


LASS-OH! 60160 92734 B
24813 9220 B

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐




15225 0360 B CONNECTION ST B

☐

15225 0360 W CONNECTION ST W


☐

Light altering devices



24814 0020 B JIHA! S B

☐



24814 0030 B JIHA! R B

☐

Notes:





LASS-OH! R65 - 3 93034 GC

24821 9320 GC

AVAILABLE IN

BLACK 24821 9320 B

GOLD COLOURED 24821 9320 GC



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	INCL.3 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 6,1W / CRI>90 (R9: 50) / 3000K / 683lm)
TM-30 VALUES	Rf: 90 / Rg: 101
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2049lm // 18,3W // 112lm/W
LED TECHNICS (LUMINAIRE)	1619lm // 21W // 77lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 1050mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



LASS-OH! R65 - 3 93034 GC



24821 9320 GC

For detailed installation instructions, please consult the manual: [24821_XXX0_HAND.pdf](#)

LASS-OH! R65 - 3 93034 GC
24821 9320 GC




FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

#

	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐

LASS-OH! R65 - 3 93034 GC

24821 9320 GC

Power box

#



24814 0075 B LASS-OH! POWERBOX H15 DIM5 B

1


☐

24814 0080 B LASS-OH! POWERBOX H15 B

1

☐

Coversets




204 00 100 B COVERSET R 100 B

☐


204 00 100 W COVERSET R 100 W

☐

Suspension parts



328 10 01 SUSPENSION TRIMLESS O.F.A.

☐

15225 0340 B SUSPENSION ST B

☐


15225 0340 W SUSPENSION ST W

☐

LASS-OH! R65 - 3 93034 GC

24821 9320 GC

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B CONNECTION ST B	☐
	15225 0360 W CONNECTION ST W	☐

Notes:





LASS-OH! R90 - 4 92734 B

24822 9220 B

AVAILABLE IN

BLACK 24822 9220 B

GOLD COLOURED 24822 9220 GC



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.1
ADJUSTABILITY	non adjustable
INFORMATION	INCL.4 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 700mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	F
CERTIFICATES	CB, ENEC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2660lm // 24,4W // 109lm/W
LED TECHNICS (LUMINAIRE)	2102lm // 28W // 75lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 700mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS



LASS-OH! R90 - 4 92734 B



24822 9220 B

For detailed installation instructions, please consult the manual: [24822_XXX0_HAND.pdf](#)

LASS-OH! R90 - 4 92734 B
24822 9220 B




FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies

#

	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐

 DELTALIGHT®

LASS-OH! R90 - 4 92734 B

24822 9220 B

Power box

#



24814 0075 B

LASS-OH! POWERBOX H15 DIM5 B

1

☐


24814 0080 B

LASS-OH! POWERBOX H15 B

1

☐

Coversets



204 00 100 B

COVERSET R 100 B


☐

204 00 100 W

COVERSET R 100 W


☐

Suspension parts



328 10 01

SUSPENSION TRIMLESS O.F.A.

☐

15225 0340 B

SUSPENSION ST B

☐

15225 0340 W



SUSPENSION ST W

☐

LASS-OH! R90 - 4 92734 B

24822 9220 B

Electric connection parts



	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B CONNECTION ST B	☐
	15225 0360 W CONNECTION ST W	☐

Notes:



LASS-OH! L150-3 92734 B
24816 9220 B

AVAILABLE IN
BLACK 24816 9220 B
GOLD COLOURED 24816 9220 GC



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	INCL.3 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	3 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	1995lm // 18,3W // 109lm/W
LED TECHNICS (LUMINAIRE)	1577lm // 21W // 75lm/W

Requirements

LASS-OH! POWERBOX
LED POWER SUPPLY 1050mA-DC DIM

Options

CABLE BASE R / S
COVERSET R 62-90-100 / S 62-80-90
CONNECTION ST / CONNECTION TRIMLESS
SUSPENSION ST / SUSPENSION TRIMLESS

LASS-OH! L150-3 92734 B

24816 9220 B

Accessories



JIHA S/R

For detailed installation instructions, please consult the manual: [24816_XXXX_HAND.pdf](#)

LASS-OH! L150-3 92734 B
24816 9220 B




FINISH YOUR SPECIFICATION

Current supply







	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies


#

	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐



LASS-OH! L150-3 92734 B
 24816 9220 B

Power box		#
 24814 0010 B LASS-OH! POWERBOX B	1	☐
 24814 0011 B LASS-OH! POWERBOX DIM1 B	1	☐
 24814 0015 B LASS-OH! POWERBOX DIM5 B	1	☐
Coversets		
 204 00 100 B COVERSET R 100 B		☐
204 00 100 W COVERSET R 100 W		☐
Suspension parts		
 328 10 01 SUSPENSION TRIMLESS O.F.A.		☐
 15225 0340 B SUSPENSION ST B		☐
15225 0340 W SUSPENSION ST W		☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B CONNECTION ST B	☐
	15225 0360 W CONNECTION ST W	☐

Light altering devices

	24814 0020 B JIHA! S B	☐
	24814 0030 B JIHA! R B	☐



Notes:



LASS-OH! L210-4 92734 B

24818 9220 B

AVAILABLE IN
BLACK 24818 9220 B
GOLD COLOURED 24818 9220 GC



 [View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.9
ADJUSTABILITY	non adjustable
INFORMATION	INCL.4 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 700mA-DC INCL.2 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	4 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	2660lm // 24,4W // 109lm/W
LED TECHNICS (LUMINAIRE)	2102lm // 28W // 75lm/W

Requirements	
LASS-OH! POWERBOX	
LED POWER SUPPLY 700mA-DC DIM	

Options	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	

LASS-OH! L210-4 92734 B

24818 9220 B

Accessories



JIHA S/R

For detailed installation instructions, please consult the manual: [24818_XXXX_HAND.pdf](#)

LASS-OH! L210-4 92734 B
24818 9220 B




FINISH YOUR SPECIFICATION

Current supply







	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐

LED power supplies



#

	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐



LASS-OH! L210-4 92734 B
 24818 9220 B

Power box		#
 24814 0010 B LASS-OH! POWERBOX B	1	☐
 24814 0011 B LASS-OH! POWERBOX DIM1 B	1	☐
 24814 0015 B LASS-OH! POWERBOX DIM5 B	1	☐
Coversets		
 204 00 100 B COVERSET R 100 B		☐
204 00 100 W COVERSET R 100 W		☐
Suspension parts		
 328 10 01 SUSPENSION TRIMLESS O.F.A.		☐
 15225 0340 B SUSPENSION ST B		☐
15225 0340 W SUSPENSION ST W		☐

Electric connection parts

	328 10 03 CONNECTION TRIMLESS O.F.A.	☐
	15225 0360 B CONNECTION ST B	☐
	15225 0360 W CONNECTION ST W	☐

Light altering devices



	24814 0020 B JIHA! S B	☐
	24814 0030 B JIHA! R B	☐

Notes:



LASS-OH! L330-6 92734 B
24819 9220 B

AVAILABLE IN
BLACK 24819 9220 B
GOLD COLOURED 24819 9220 GC



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.4
ADJUSTABILITY	non adjustable
INFORMATION	INCL.6 x DOT.COM S6 modules per module: 6 x REFLECTOR FL-34° EXCL.LED POWER SUPPLY 1050mA-DC INCL.3 x CABLE SUSPENSION SINGLE AUTO. 1,6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info	
CLASS	III
DIM TYPE	depending on power supply
ENERGY CLASS	E
CERTIFICATES	EAC

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	6 x (LED cluster 6,1W / CRI>90 (R9: 50) / 2700K / 665lm)
TM-30 VALUES	Rf: 92 / Rg: 100
SDCM	SDCM3
LM80	L80 > 60000
LED TECHNICS (LIGHT SOURCE)	3990lm // 36,6W // 109lm/W
LED TECHNICS (LUMINAIRE)	3153lm // 42W // 75lm/W

Requirements	
LASS-OH! POWERBOX	
LED POWER SUPPLY 1050mA-DC DIM	

Options	
CABLE BASE R / S	
COVERSET R 62-90-100 / S 62-80-90	
CONNECTION ST / CONNECTION TRIMLESS	
SUSPENSION ST / SUSPENSION TRIMLESS	

LASS-OH! L330-6 92734 B

24819 9220 B

Accessories



JIHA S/R

For detailed installation instructions, please consult the manual: [24819_XXXX_HAND.pdf](#)

LASS-OH! L330-6 92734 B
24819 9220 B




FINISH YOUR SPECIFICATION

Current supply

	203 99 55 ANO CABLE BASE R ANO	☐
	203 99 55 B CABLE BASE R B	☐
	203 99 55 W CABLE BASE R W	☐
	203 99 56 ANO CABLE BASE S ANO	☐
	203 99 56 B CABLE BASE S B	☐
	203 99 56 W CABLE BASE S W	☐


LED power supplies

#

	21012 0010 LED POWER SUPPLY MULTI POWER	1 ☐
	21012 0021 LED POWER SUPPLY MULTI POWER DIM1	1 ☐
	21012 0035 LED POWER SUPPLY MULTI POWER DIM5	1 ☐


LASS-OH! L330-6 92734 B
 24819 9220 B

Power box
#




24814 0010 B
LASS-OH! POWERBOX B

1
☐



24814 0011 B
LASS-OH! POWERBOX DIM1 B


1
☐



24814 0015 B
LASS-OH! POWERBOX DIM5 B

1
☐

Coversets




204 00 100 B
COVERSET R 100 B

☐

204 00 100 W
COVERSET R 100 W


☐

Suspension parts



328 10 01
SUSPENSION TRIMLESS O.F.A.

☐



15225 0340 B
SUSPENSION ST B

☐


15225 0340 W
SUSPENSION ST W

☐

LASS-OH! L330-6 92734 B

24819 9220 B

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐


15225 0360 B CONNECTION ST B

☐


15225 0360 W CONNECTION ST W

☐

Light altering devices



24814 0020 B JIHA! S B

☐

24814 0030 B JIHA! R B

☐

Notes: