





SPY C 93033 DIM8 W

279 776 811 932 ED8 W

AVAILABLE IN
BLACK 279 776 811 932 ED8 B
WHITE 279 776 811 932 ED8 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR FL-33° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE SUSPENSION SINGLE AUTO. 1.6m INCL.1 x CABLE 2 x 0.75mm ²

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	I
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	C
CERTIFICATES	CB, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	404lm // 7W // 61lm/W

Requirements

SPY TUBE

Options

SUSPENSION + CONNECTION TRIMLESS

SPY C 93033 DIM8 W

279 776 811 932 ED8 W

Accessories

HONEYCOMB 50

LINEAR SPREAD LENS 50

SPREAD LENS 50

SOFTENING LENS 50


GLASS SBL 50

For detailed installation instructions, please consult the manual: [279_776_811_XXX_ED8_HAND.pdf](#)

SPY C 93033 DIM8 W
279 776 811 932 ED8 W

FINISH YOUR SPECIFICATION


Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Suspension parts




328 10 02 SUSPENSION + CONNECTION TRIMLESS O.F.A.

☐


Light altering devices




413 03 01 B HONEYCOMB 50 B

☐


413 03 02 LINEAR SPREAD LENS 50

☐

413 03 03 SPREAD LENS 50

☐

413 03 04 SOFTENING LENS 50

☐

413 03 05 GLASS SBL 50

☐

⌵ DELTALIGHT®

SPY C 93033 DIM8 W

279 776 811 932 ED8 W

Finish your product

	53 414 01 00 B	SPY TUBE B	☐
	414 01 00 FBR	SPY TUBE FBR	☐
	414 01 00 FG	SPY TUBE FG	☐
	414 01 00 MMAT	SPY TUBE MMAT	☐
	414 01 00 SG	SPY TUBE SG	☐
	414 01 00 W	SPY TUBE W	☐

Notes:





MICROSPY 39 C 92745 B

279 773 811 921 B

AVAILABLE IN

BLACK 279 773 811 921 B

WHITE 279 773 811 921 W



[View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm ² / 1,6m

Electrical info

ELECTRICAL	110-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUPE	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 7W // 76lm/W

Options

CONNECTION TRIMLESS


For detailed installation instructions, please consult the manual: [279_773_811_XXX_HAND.pdf](#)

MICROSPY 39 C 92745 B

279 773 811 921 B

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Notes: