





## SUPER-OH! SLIM 80 CS SBL DOWN 930 B

20733 9300 B

AVAILABLE IN

**BLACK** 20733 9300 B

**WHITE** 20733 9300 W



[View on website](#)



### General info

|                           |                                                                                                                       |
|---------------------------|-----------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                     |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                  |
| <b>WEIGHT (KG)</b>        | 5,1                                                                                                                   |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                        |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.LED POWER SUPPLY 900mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | C                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4570lm |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 4570lm // 28,6W // 159lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 2961lm // 33W // 90lm/W                              |

For detailed installation instructions, please consult the manual: [20733\\_XXX0\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 CS SBL DOWN 930 B**

20733 9300 B



Notes:



## SUPER-OH! SLIM 120 CS SBL DOWN 930 W

20734 9300 W

AVAILABLE IN  
**BLACK** 20734 9300 B  
**WHITE** 20734 9300 W



[View on website](#)



### General info

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                 |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                      |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                   |
| <b>WEIGHT (KG)</b>        | 6.7                                                                                                                    |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                         |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.LED POWER SUPPLY 1400mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 44,6W / CRI>90 (R9: 50) / 3000K / 7085lm |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 7085lm // 44,6W // 159lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4733lm // 51W // 92lm/W                              |

For detailed installation instructions, please consult the manual: [20734\\_XXX0\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 CS SBL DOWN 930 W**

20734 9300 W

Notes:





## SUPER-OH! SLIM 80 CS SBL DOWN-UP 930 B

20735 9300 B

AVAILABLE IN

**BLACK** 20735 9300 B

**WHITE** 20735 9300 W



[View on website](#)

### General info

|                           |                                                                                                                                                                                      |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                               |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                    |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                 |
| <b>WEIGHT (KG)</b>        | 5,4                                                                                                                                                                                  |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                       |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.LED POWER SUPPLY 900mA<br>UP: INCL.LED POWER SUPPLY 700mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                              |                    |
|------------------------------|--------------------|
| <b>ELECTRICAL</b>            | 220-240V / 50-60Hz |
| <b>CLASS</b>                 | I                  |
| <b>POWER SUPPLY INCLUDED</b> | YES                |
| <b>DIM TYPE</b>              | non-dimmable       |
| <b>ENERGY CLASS</b>          | D                  |
| <b>CERTIFICATES</b>          | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                    |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4570lm<br>UP: LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3542lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                  |
| <b>LM80</b>                        | L80 > 60000                                                                                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 4570lm // 28,6W // 159lm/W<br>UP: 3542lm // 22,3W // 159lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 2961lm // 33W // 90lm/W<br>UP: 2699lm // 26W // 105lm/W                                                          |

For detailed installation instructions, please consult the manual: [20735\\_XXX0\\_HAND.pdf](#)



**SUPER-OH! SLIM 80 CS SBL DOWN-UP 930 B**

20735 9300 B



Notes:



## SUPER-OH! SLIM 80 HP CS SBL DOWN 930 W

20741 9300 W

AVAILABLE IN  
**BLACK** 20741 9300 B  
**WHITE** 20741 9300 W



[View on website](#)

### General info

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                 |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                      |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                   |
| <b>WEIGHT (KG)</b>        | 5.1                                                                                                                    |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                         |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.LED POWER SUPPLY 1400mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                              |                    |
|------------------------------|--------------------|
| <b>ELECTRICAL</b>            | 220-240V / 50-60Hz |
| <b>CLASS</b>                 | I                  |
| <b>POWER SUPPLY INCLUDED</b> | YES                |
| <b>DIM TYPE</b>              | non-dimmable       |
| <b>ENERGY CLASS</b>          | D                  |
| <b>CERTIFICATES</b>          | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 45,9W / CRI>90 (R9: 50) / 3000K / 7008lm |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 7008lm // 45,9W // 153lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4541lm // 53W // 86lm/W                              |

For detailed installation instructions, please consult the manual: [20741\\_XXX0\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 HP CS SBL DOWN 930 W**

20741 9300 W

Notes:





## SUPER-OH! SLIM 120 CS SBL DOWN-UP 930 B

20736 9300 B

AVAILABLE IN

**BLACK** 20736 9300 B

**WHITE** 20736 9300 W



[View on website](#)



### General info

|                           |                                                                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                                 |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                      |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                   |
| <b>WEIGHT (KG)</b>        | 7.1                                                                                                                                                                                    |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                         |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.LED POWER SUPPLY 1400mA<br>UP: INCL.LED POWER SUPPLY 1050mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                    |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 44,6W / CRI>90 (R9: 50) / 3000K / 7085lm<br>UP: LED cluster 33,1W / CRI>90 (R9: 50) / 3000K / 5304lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                  |
| <b>LM80</b>                        | L80 > 60000                                                                                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 7085lm // 44,6W // 159lm/W<br>UP: 5304lm // 33,1W // 160lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 4733lm // 51W // 92lm/W<br>UP: 4010lm // 38W // 105lm/W                                                          |

For detailed installation instructions, please consult the manual: [20736\\_XXX0\\_HAND.pdf](#)



**SUPER-OH! SLIM 120 CS SBL DOWN-UP 930 B**

20736 9300 B



Notes:



## SUPER-OH! SLIM 120 HP CS SBL DOWN 930 W

20742 9300 W

AVAILABLE IN  
**BLACK** 20742 9300 B  
**WHITE** 20742 9300 W



[View on website](#)



### General info

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                 |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                      |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                   |
| <b>WEIGHT (KG)</b>        | 6.7                                                                                                                    |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                         |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.LED POWER SUPPLY 2100mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                   |
| <b>LIGHTSOURCE</b>                 | LED cluster 68,8W / CRI>90 (R9: 50) / 3000K / 10512lm |
| <b>SDCM</b>                        | SDCM3                                                 |
| <b>LM80</b>                        | L80 > 60000                                           |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 10512lm // 68,8W // 153lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 7022lm // 79W // 89lm/W                               |

For detailed installation instructions, please consult the manual: [20742\\_XXX0\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 HP CS SBL DOWN 930 W**

20742 9300 W

Notes:





## SUPER-OH! SLIM 120 HP CS SBL DOWN 930 B

20742 9300 B

AVAILABLE IN

**BLACK** 20742 9300 B

**WHITE** 20742 9300 W



[View on website](#)



### General info

|                           |                                                                                                                        |
|---------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                 |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                      |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                   |
| <b>WEIGHT (KG)</b>        | 6.7                                                                                                                    |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                         |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.LED POWER SUPPLY 2100mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                   |
| <b>LIGHTSOURCE</b>                 | LED cluster 68,8W / CRI>90 (R9: 50) / 3000K / 10512lm |
| <b>SDCM</b>                        | SDCM3                                                 |
| <b>LM80</b>                        | L80 > 60000                                           |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 10512lm // 68,8W // 153lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 7022lm // 79W // 89lm/W                               |

For detailed installation instructions, please consult the manual: [20742\\_XXX0\\_HAND.pdf](#)



**SUPER-OH! SLIM 120 HP CS SBL DOWN 930 B**

20742 9300 B



Notes:



## SUPER-OH! SLIM 80 CS SBL DOWN 930 DIM4 W

20733 9304 W

AVAILABLE IN  
**BLACK** 20733 9304 B  
**WHITE** 20733 9304 W



[View on website](#)



### General info

|                           |                                                                                                                                |
|---------------------------|--------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                         |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                              |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                           |
| <b>WEIGHT (KG)</b>        | 5.1                                                                                                                            |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                 |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY 900mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | C                          |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4570lm |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 4570lm // 28,6W // 159lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 2961lm // 33W // 90lm/W                              |

For detailed installation instructions, please consult the manual: [20733\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 CS SBL DOWN 930 DIM4 W**

20733 9304 W



Notes:



## SUPER-OH! SLIM 120 CS SBL DOWN 930 DIM4 W

20734 9304 W

AVAILABLE IN  
**BLACK** 20734 9304 B  
**WHITE** 20734 9304 W



[View on website](#)



### General info

|                           |                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                          |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                               |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                            |
| <b>WEIGHT (KG)</b>        | 6.7                                                                                                                             |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                  |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY 1400mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | D                          |

### Lightsource info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 44,6W / CRI>90 (R9: 50) / 3000K / 7085lm |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 7085lm // 44,6W // 159lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4733lm // 51W // 92lm/W                              |

For detailed installation instructions, please consult the manual: [20734\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 CS SBL DOWN 930 DIM4 W**

20734 9304 W



Notes:



## SUPER-OH! SLIM 80 HP CS SBL DOWN-UP 930 W

20743 9300 W

AVAILABLE IN  
**BLACK** 20743 9300 B  
**WHITE** 20743 9300 W



[View on website](#)



### General info

|                           |                                                                                                                                                                                       |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                                |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                     |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                  |
| <b>WEIGHT (KG)</b>        | 5.4                                                                                                                                                                                   |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                        |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.LED POWER SUPPLY 1400mA<br>UP: INCL.LED POWER SUPPLY 700mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                    |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 45,9W / CRI>90 (R9: 50) / 3000K / 7008lm<br>UP: LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3542lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                  |
| <b>LM80</b>                        | L80 > 60000                                                                                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 7008lm // 45,9W // 153lm/W<br>UP: 3542lm // 22,3W // 159lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 4541lm // 53W // 86lm/W<br>UP: 2699lm // 26W // 105lm/W                                                          |

For detailed installation instructions, please consult the manual: [20743\\_XXX0\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 HP CS SBL DOWN-UP 930 W**

20743 9300 W



Notes:



## SUPER-OH! SLIM 120 HP CS SBL DOWN-UP 930 B

20744 9300 B

AVAILABLE IN  
**BLACK** 20744 9300 B  
**WHITE** 20744 9300 W



[View on website](#)

### General info

|                           |                                                                                                                                                                                        |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                                 |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                      |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                   |
| <b>WEIGHT (KG)</b>        | 7.1                                                                                                                                                                                    |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                         |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.LED POWER SUPPLY 2100mA<br>UP: INCL.LED POWER SUPPLY 1050mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                     |                    |
|---------------------|--------------------|
| <b>ELECTRICAL</b>   | 220-240V / 50-60Hz |
| <b>CLASS</b>        | I                  |
| <b>POWER SUPPLY</b> | YES                |
| <b>DIM TYPE</b>     | non-dimmable       |
| <b>ENERGY CLASS</b> | D                  |
| <b>CERTIFICATES</b> | CB, ENEC, RCM      |

### Lightsource info

|                                    |                                                                                                                         |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                     |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 68,8W / CRI>90 (R9: 50) / 3000K / 10512lm<br>UP: LED cluster 33,1W / CRI>90 (R9: 50) / 3000K / 5304lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                   |
| <b>LM80</b>                        | L80 > 60000                                                                                                             |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 10512lm // 68,8W // 153lm/W<br>UP: 5304lm // 33,1W // 160lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 7022lm // 79W // 89lm/W<br>UP: 4010lm // 38W // 105lm/W                                                           |

For detailed installation instructions, please consult the manual: [20744\\_XXX0\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 HP CS SBL DOWN-UP 930 B**

20744 9300 B



Notes:



## SUPER-OH! SLIM 80 CS SBL DOWN-UP 930 DIM4 W

20735 9304 W

AVAILABLE IN  
**BLACK** 20735 9304 B  
**WHITE** 20735 9304 W



[View on website](#)



| General info                |                                                                                                                                                                                                        |
|-----------------------------|--------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| LOCATION                    | indoor                                                                                                                                                                                                 |
| INSTALLATION                | Ceiling Suspended                                                                                                                                                                                      |
| INGRESS PROTECTION          | IP20                                                                                                                                                                                                   |
| WEIGHT (KG)                 | 3,2                                                                                                                                                                                                    |
| ADJUSTABILITY               | non adjustable                                                                                                                                                                                         |
| INFORMATION                 | INCL.PC SBL<br>DOWN: INCL.DIMMABLE LED POWER SUPPLY 900mA<br>UP: INCL.DIMMABLE LED POWER SUPPLY 700mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |
| Electrical info             |                                                                                                                                                                                                        |
| ELECTRICAL                  | 220-240V / 0 50-60Hz                                                                                                                                                                                   |
| CLASS                       | I                                                                                                                                                                                                      |
| POWER SUPPLY INCLUDED       | YES                                                                                                                                                                                                    |
| DIM TYPE                    | DALI or DSI or push button                                                                                                                                                                             |
| ENERGY CLASS                | D                                                                                                                                                                                                      |
| Lightsource info            |                                                                                                                                                                                                        |
| LIGHTSOURCE NAME            | LED                                                                                                                                                                                                    |
| LIGHTSOURCE                 | DOWN: LED cluster 28,6W / CRI>90 (R9: 50) / 3000K / 4570lm<br>UP: LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3542lm                                                                                 |
| SDCM                        | SDCM3                                                                                                                                                                                                  |
| LM80                        | L80 > 60000                                                                                                                                                                                            |
| LED TECHNICS (LIGHT SOURCE) | DOWN: 4570lm // 28,6W // 159lm/W<br>UP: 3542lm // 22,3W // 159lm/W                                                                                                                                     |
| LED TECHNICS (LUMINAIRE)    | DOWN: 2961lm // 33W // 90lm/W<br>UP: 2699lm // 26W // 105lm/W                                                                                                                                          |

For detailed installation instructions, please consult the manual: [20735\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 CS SBL DOWN-UP 930 DIM4 W**

20735 9304 W



Notes:



## SUPER-OH! SLIM 80 HP CS SBL DOWN 930 DIM4 B

20741 9304 B

AVAILABLE IN  
**BLACK** 20741 9304 B  
**WHITE** 20741 9304 W



[View on website](#)



### General info

|                           |                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                          |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                               |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                            |
| <b>WEIGHT (KG)</b>        | 5.1                                                                                                                             |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                  |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY 1400mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | D                          |

### Lightsources info

|                                    |                                                      |
|------------------------------------|------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                  |
| <b>LIGHTSOURCE</b>                 | LED cluster 45,9W / CRI>90 (R9: 50) / 3000K / 7008lm |
| <b>SDCM</b>                        | SDCM3                                                |
| <b>LM80</b>                        | L80 > 60000                                          |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 7008lm // 45,9W // 153lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 4541lm // 53W // 86lm/W                              |

For detailed installation instructions, please consult the manual: [20741\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 HP CS SBL DOWN 930 DIM4 B**

20741 9304 B



Notes:



## SUPER-OH! SLIM 120 CS SBL DOWN-UP 930 DIM4 W

20736 9304 W

AVAILABLE IN  
**BLACK** 20736 9304 B  
**WHITE** 20736 9304 W



[View on website](#)

### General info

|                           |                                                                                                                                                                                                          |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                                                   |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                                        |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                                     |
| <b>WEIGHT (KG)</b>        | 7.1                                                                                                                                                                                                      |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                                           |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.DIMMABLE LED POWER SUPPLY 1400mA<br>UP: INCL.DIMMABLE LED POWER SUPPLY 1050mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | D                          |

### Lightsource info

|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                    |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 44,6W / CRI>90 (R9: 50) / 3000K / 7085lm<br>UP: LED cluster 33,1W / CRI>90 (R9: 50) / 3000K / 5304lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                  |
| <b>LM80</b>                        | L80 > 60000                                                                                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 7085lm // 44,6W // 159lm/W<br>UP: 5304lm // 33,1W // 160lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 4733lm // 51W // 92lm/W<br>UP: 4010lm // 38W // 105lm/W                                                          |

For detailed installation instructions, please consult the manual: [20736\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 CS SBL DOWN-UP 930 DIM4 W**

20736 9304 W



Notes:



## SUPER-OH! SLIM 120 HP CS SBL DOWN 930 DIM4 B

20742 9304 B

AVAILABLE IN  
**BLACK** 20742 9304 B  
**WHITE** 20742 9304 W



[View on website](#)



### General info

|                           |                                                                                                                                 |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                          |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                               |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                            |
| <b>WEIGHT (KG)</b>        | 6.7                                                                                                                             |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                  |
| <b>INFORMATION</b>        | INCL.PC SBL<br>INCL.DIMMABLE LED POWER SUPPLY 2100mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | D                          |

### Lightsource info

|                                    |                                                       |
|------------------------------------|-------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                   |
| <b>LIGHTSOURCE</b>                 | LED cluster 68,8W / CRI>90 (R9: 50) / 3000K / 10512lm |
| <b>SDCM</b>                        | SDCM3                                                 |
| <b>LM80</b>                        | L80 > 60000                                           |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | 10512lm // 68,8W // 153lm/W                           |
| <b>LED TECHNICS (LUMINAIRE)</b>    | 7022lm // 79W // 89lm/W                               |

For detailed installation instructions, please consult the manual: [20742\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 HP CS SBL DOWN 930 DIM4 B**

20742 9304 B



Notes:



## SUPER-OH! SLIM 80 HP CS SBL DOWN-UP 930 DIM4 W

20743 9304 W

AVAILABLE IN  
**BLACK** 20743 9304 B  
**WHITE** 20743 9304 W



[View on website](#)

### General info

|                           |                                                                                                                                                                                                         |
|---------------------------|---------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                                                  |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                                       |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                                    |
| <b>WEIGHT (KG)</b>        | 4.4                                                                                                                                                                                                     |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                                          |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.DIMMABLE LED POWER SUPPLY 1400mA<br>UP: INCL.DIMMABLE LED POWER SUPPLY 700mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | D                          |

### Lightsource info

|                                    |                                                                                                                        |
|------------------------------------|------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                    |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 45,9W / CRI>90 (R9: 50) / 3000K / 7008lm<br>UP: LED cluster 22,3W / CRI>90 (R9: 50) / 3000K / 3542lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                  |
| <b>LM80</b>                        | L80 > 60000                                                                                                            |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 7008lm // 45,9W // 153lm/W<br>UP: 3542lm // 22,3W // 159lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 4541lm // 53W // 86lm/W<br>UP: 2699lm // 26W // 105lm/W                                                          |

For detailed installation instructions, please consult the manual: [20743\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 80 HP CS SBL DOWN-UP 930 DIM4 W**

20743 9304 W



Notes:



## SUPER-OH! SLIM 120 HP CS SBL DOWN-UP 930 DIM4 B

20744 9304 B

AVAILABLE IN  
**BLACK** 20744 9304 B  
**WHITE** 20744 9304 W



[View on website](#)

### General info

|                           |                                                                                                                                                                                                          |
|---------------------------|----------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------------|
| <b>LOCATION</b>           | indoor                                                                                                                                                                                                   |
| <b>INSTALLATION</b>       | Ceiling Suspended                                                                                                                                                                                        |
| <b>INGRESS PROTECTION</b> | IP20                                                                                                                                                                                                     |
| <b>WEIGHT (KG)</b>        | 7.1                                                                                                                                                                                                      |
| <b>ADJUSTABILITY</b>      | non adjustable                                                                                                                                                                                           |
| <b>INFORMATION</b>        | INCL.PC SBL<br>DOWN: INCL.DIMMABLE LED POWER SUPPLY 2100mA<br>UP: INCL.DIMMABLE LED POWER SUPPLY 1050mA<br>INCL.4 x CABLE SUSPENSION SINGLE AUTO. 3m<br>POWER VIA CABLE SUSPENSION<br>CABLING 2 CIRCUITS |

### Electrical info

|                              |                            |
|------------------------------|----------------------------|
| <b>ELECTRICAL</b>            | 220-240V / 0 50-60Hz       |
| <b>CLASS</b>                 | I                          |
| <b>POWER SUPPLY INCLUDED</b> | YES                        |
| <b>DIM TYPE</b>              | DALI or DSI or push button |
| <b>ENERGY CLASS</b>          | D                          |

### Lightsource info

|                                    |                                                                                                                         |
|------------------------------------|-------------------------------------------------------------------------------------------------------------------------|
| <b>LIGHTSOURCE NAME</b>            | LED                                                                                                                     |
| <b>LIGHTSOURCE</b>                 | DOWN: LED cluster 68,8W / CRI>90 (R9: 50) / 3000K / 10512lm<br>UP: LED cluster 33,1W / CRI>90 (R9: 50) / 3000K / 5304lm |
| <b>SDCM</b>                        | SDCM3                                                                                                                   |
| <b>LM80</b>                        | L80 > 60000                                                                                                             |
| <b>LED TECHNICS (LIGHT SOURCE)</b> | DOWN: 10512lm // 68,8W // 153lm/W<br>UP: 5304lm // 33,1W // 160lm/W                                                     |
| <b>LED TECHNICS (LUMINAIRE)</b>    | DOWN: 7022lm // 79W // 89lm/W<br>UP: 4010lm // 38W // 105lm/W                                                           |

For detailed installation instructions, please consult the manual: [20744\\_XXX4\\_HAND.pdf](#)



## **SUPER-OH! SLIM 120 HP CS SBL DOWN-UP 930 DIM4 B**

20744 9304 B

Notes: