





HEDRA 391 C 93045 W

472 121 811 931 W

AVAILABLE IN
BLACK 472 121 811 931 B
BLACK BRONZE 472 121 811 931 BBR
GOLD COLOURED 472 121 811 931 GC
WHITE 472 121 811 931 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm² / 1,6m
Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	C
CERTIFICATES	CB, EAC, ENEC, RCM
Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 52) / 3000K / 787lm
TM-30 VALUES	rf: 90 / Rg: 99
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	787lm // 5,8W // 135lm/W
LED TECHNICS (LUMINAIRE)	530lm // 7W // 79lm/W
Options	
CONNECTION TRIMLESS	


HEDRA 391 C 93045 W

472 121 811 931 W

For detailed installation instructions, please consult the manual: [472_121_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Notes:



HEDRA 392 C 92745 B

472 122 811 921 B



AVAILABLE IN

BLACK 472 122 811 921 B

BLACK BRONZE 472 122 811 921 BBR

GOLD COLOURED 472 122 811 921 GC

WHITE 472 122 811 921 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.2
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm ² / 1,6m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 7W // 76lm/W

Options

CONNECTION TRIMLESS


HEDRA 392 C 92745 B

472 122 811 921 B

For detailed installation instructions, please consult the manual: [472_122_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Notes:



HEDRA 393 C 92745 BBR

472 123 811 921 BBR



AVAILABLE IN

BLACK 472 123 811 921 B

BLACK BRONZE 472 123 811 921 BBR

GOLD COLOURED 472 123 811 921 GC

WHITE 472 123 811 921 W



 [View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm ² / 1,6m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 7W // 76lm/W

Options

CONNECTION TRIMLESS


HEDRA 393 C 92745 BBR

472 123 811 921 BBR

For detailed installation instructions, please consult the manual: [472_123_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Notes:



HEDRA 393 C 92745 W

472 123 811 921 W



AVAILABLE IN

BLACK 472 123 811 921 B

BLACK BRONZE 472 123 811 921 BBR

GOLD COLOURED 472 123 811 921 GC

WHITE 472 123 811 921 W



[View on website](#)



General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	1.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-45° INCL.LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm ² / 1,6m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	non-dimmable
ENERGY CLASS	D
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 5,8W / CRI>90 (R9: 60) / 2700K / 753lm
TM-30 VALUES	rf: 89 / Rg: 100
SDCM	SDCM1
RISKGROUP	RG1
LM80	L90B10 > 50000
LED TECHNICS (LIGHT SOURCE)	753lm // 5,8W // 129lm/W
LED TECHNICS (LUMINAIRE)	507lm // 7W // 76lm/W

Options

CONNECTION TRIMLESS


HEDRA 393 C 92745 W

472 123 811 921 W

For detailed installation instructions, please consult the manual: [472_123_811_XXX_HAND.pdf](#)

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐



Notes:



HEDRA 451 C 92740 DIM8 B

472 221 922 ED8 B

AVAILABLE IN
BLACK 472 221 922 ED8 B
BLACK BRONZE 472 221 922 ED8 BBR
GOLD COLOURED 472 221 922 ED8 GC
WHITE 472 221 922 ED8 W




[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.6
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm² / 1,6m

Electrical info	
ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info	
LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 2700K / 587lm
SDCM	SDCM2
RISKGROUP	RG1
LED TECHNICS (LIGHT SOURCE)	587lm // 6,4W // 92lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7W // 66lm/W

Requirements	
MIDISPY TUBE	

Options	
CONNECTION TRIMLESS	



HEDRA 451 C 92740 DIM8 B

472 221 922 ED8 B


For detailed installation instructions, please consult the manual: [**472_221_XXX_ED8_HAND.pdf**](#)

HEDRA 451 C 92740 DIM8 B

472 221 922 ED8 B

FINISH YOUR SPECIFICATION


Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts




328 10 03 CONNECTION TRIMLESS O.F.A.

☐

HEDRA 451 C 92740 DIM8 B

472 221 922 ED8 B

Finish your product



	414 03 00 B	MIDISPY TUBE B	☐
	414 03 00 FBR	MIDISPY TUBE FBR	☐
	414 03 00 FG	MIDISPY TUBE FG	☐
	414 03 00 MMAT	MIDISPY TUBE MMAT	☐
	414 03 00 SG	MIDISPY TUBE SG	☐
	414 03 00 W	MIDISPY TUBE W	☐

Notes:



HEDRA 452 C 93040 DIM8 BBR
472 222 932 ED8 BBR

AVAILABLE IN
BLACK 472 222 932 ED8 B
BLACK BRONZE 472 222 932 ED8 BBR
GOLD COLOURED 472 222 932 ED8 GC
WHITE 472 222 932 ED8 W



 [View on website](#)

General info

LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.8
ADJUSTABILITY	non adjustable
INFORMATION	REFLECTOR WFL-40° INCL.DIMMABLE LED POWER SUPPLY 350mA-DC INCL.1 x CABLE 2 x 0.75mm² / 1,6m

Electrical info

ELECTRICAL	220-240V / 50-60Hz
CLASS	II
POWER SUPPLY	YES
DIM TYPE	mains (phase cut-off)
ENERGY CLASS	F
CERTIFICATES	CB, EAC, ENEC, RCM

Lightsource info

LIGHTSOURCE NAME	LED
LIGHTSOURCE	LED array 6,4W / CRI>90 / 3000K / 587lm
SDCM	SDCM2
RISKGROUP	RG1
LED TECHNICS (LIGHT SOURCE)	587lm // 6,4W // 92lm/W
LED TECHNICS (LUMINAIRE)	488lm // 7W // 66lm/W

Requirements

MIDISPY TUBE

Options

CONNECTION TRIMLESS



HEDRA 452 C 93040 DIM8 BBR

472 222 932 ED8 BBR


For detailed installation instructions, please consult the manual: [472_222_XXX_ED8_HAND.pdf](#)

HEDRA 452 C 93040 DIM8 BBR

472 222 932 ED8 BBR

FINISH YOUR SPECIFICATION


Miscellaneous control equipment



300 90 004 ED8 WIRELESS CONTROL DIM8

☐


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts




328 10 03 CONNECTION TRIMLESS O.F.A.

☐

 DELTALIGHT[®]

HEDRA 452 C 93040 DIM8 BBR
472 222 932 ED8 BBR

Finish your product



	<u>414 03 00 B</u>	MIDISPY TUBE B	☐
	<u>414 03 00 FBR</u>	MIDISPY TUBE FBR	☐
	<u>414 03 00 FG</u>	MIDISPY TUBE FG	☐
	<u>414 03 00 MMAT</u>	MIDISPY TUBE MMAT	☐
	<u>414 03 00 SG</u>	MIDISPY TUBE SG	☐
	<u>414 03 00 W</u>	MIDISPY TUBE W	☐

Notes:



HEDRA 451 C E27 GC
472 221 01 GC

AVAILABLE IN
BLACK 472 221 01 B
BLACK BRONZE 472 221 01 BBR
GOLD COLOURED 472 221 01 GC
WHITE 472 221 01 W



[View on website](#)



General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.5
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x CABLE 2 x 0.75mm ² / 1,6m
Electrical info	
	1 x LED Filament max.20W
CLASS	II
Lightsource info	
LIGHTSOURCE NAME	E27
Remarks	
lamp not included	
Options	
CONNECTION TRIMLESS	


For detailed installation instructions, please consult the manual: [472_221_01_HAND.pdf](#)

HEDRA 451 C E27 GC

472 221 01 GC

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.



☐

Notes:



HEDRA 452 C E27 B
472 222 01 B

AVAILABLE IN
BLACK 472 222 01 B
BLACK BRONZE 472 222 01 BBR
GOLD COLOURED 472 222 01 GC
WHITE 472 222 01 W



 [View on website](#)

General info	
LOCATION	indoor
INSTALLATION	Ceiling Suspended
INGRESS PROTECTION	IP20
WEIGHT (KG)	0.7
ADJUSTABILITY	non adjustable
INFORMATION	INCL.1 x CABLE 2 x 0.75mm ² / 1,6m

Electrical info	
	1 x LED Filament max.20W
CLASS	II

Lightsource info	
LIGHTSOURCE NAME	E27

Remarks	
lamp not included	

Options	
CONNECTION TRIMLESS	


For detailed installation instructions, please consult the manual: [472_222_01_HAND.pdf](#)

HEDRA 452 C E27 B

472 222 01 B

FINISH YOUR SPECIFICATION


Suspension parts



15229 0010 B CABLE CLAMP B

☐

Electric connection parts



328 10 03 CONNECTION TRIMLESS O.F.A.

☐

Notes: